

VALVES

US SOLENOID VALVES



● US-50



● US-40



● US-25



● US-20



● US-15

DESCRIPTION

US Solenoid valves have a hard Teflon seal and will operate at high temperature and pressure. The body is bronze and has a large flow capacity. The valve is easy to maintain and comes in various operating voltages. Valves must be installed horizontally.

SPEC/MODEL	US-10	US-15	US-20	US-25	US-35	US-40	US-50
CONNECTION BSP	3/8	1/2	3/4	1	1 1/4	1 1/2	2
NOMINAL DIAM mm	17	17	17	20	30	30	50
BODY MATERIAL	BRONZE						
OPERATION	PLUNGER / PILOT						
MEDIUM	AIR, WATER, OIL (Below 50 CST), STEAM						
PRESSURE	0.1~15 BAR (10 BAR STEAM)						
TEMPERATURE	0~185°C						
VOLTAGE	ACV 12, 24, 36, 110, 220, 380. DCV 12, 24, 110.						
VOLTAGE RANGE	± 10%						
MIN. ACTIVATE TIME	0.05 Sec.						
INSTALLATION	HORIZONTAL						

MODEL	A	B	C	D	E	F
UWS-15	83	146	21	70	42	1/2"
UWS-20	83	146	21	70	42	3/4"
UWS-25	90	162	26	70	52	1"
UWS-35	110	183	36	70	74	1 1/4"
UWS-40	110	183	36	70	74	1 1/2"
UWS-50	163	223	47	70	95	2"

